

View Online at <https://aerobasegroup.com/nsn/5905-01-123-2027>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Terminal Length:

0.300 inches

Mounting Slot Width:

0.062 inches

Shaft Diameter:

0.060 inches

Shaft Length:

0.040 inches

Body Length:

0.375 inches

Body Width:

0.150 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Rugged

Lateral Distance Between Mounting Hole Centers:

0.419 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side two rows

Mounting Method:

Slot and terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

2.5 gallons per minute c and better flooring

Rotary Actuator Travel In Angular Deg:

7920.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0