

View Online at <https://aerobasegroup.com/nsn/5905-01-123-5987>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.3120 inches

Pilot Length:

0.0620 inches

Overall Length:

4.667 inches

Undercut Diameter:

1.313 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.437 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.812 inches

Body Length:

2.820 inches

Overall Diameter:

2.188 inches

Mounting Lip Diameter:

1.4370 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

2.40 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Mechanical Backlash In Deg Angular Rotation:

1.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Cubic Measure:

4.574 cubic inches

Electrical Resistance Per Section:

5.0 kilohms all sections

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

174.5 all sections

Rotary Actuator Travel In Angular Deg:

350.0

Resistance Temperature Characteristic Range Per Section In Percent:

-5.0/+5.0 -65 degrees celsius all sections and -4.0/+4.0 -15 degrees celsius all sections and -2.5/+2.5 50 degrees celsius all sections and -5.0/+5.0 75 degrees celsius all sections and -5.0/+5.0 105 degrees celsius all sections and -5.0/+5.0 125 degrees celsius all sections

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

1.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation all sections

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

9 oclock all primaries

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Unpackaged Unit Weight:

6.00 ounces

Test Data Document:

80064-845-4687683 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0