NSN 5905-01-124-8449

Film Fixed Resistor - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5905-01-124-8449

Tompurature Coefficient Of Resistance in Ppm Per Deg Celsius:
Electrical Resistance: 909.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: -55.0/+150.0 Inclosure Method: -61.0 Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Diameter: 0.190 inches Power Dissipation Rating In Watts: 1.500 opens Power Dissipation Rating In Watts: 1.500 og ms Style Designator: Axial terminal each end
999.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 ogms Style Designator: Axial terminal each end
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.500 grams Style Designator: Axial terminal each end
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Diameter: 0.190 inches Body Dismeter: 0.190 inches Body
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 toches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
0.010 Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Terminal Length: 1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
1.500 inches Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
0.562 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
1.000 free air Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
Unpackaged Unit Weight: 1.500 grams Style Designator: Axial terminal each end
1.500 grams Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39017/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5905-01-124-8449

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0