

View Online at <https://aerobasegroup.com/nsn/5905-01-124-8459>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.688 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

Between 0.0932 inches and 0.0935 inches

**Shaft Length:**

0.688 inches

**Mounting Bushing Length:**

0.221 inches

**Body Length:**

1.000 inches

**Overall Diameter:**

0.938 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Shaft Radial Play:**

0.003 inches

**Fragility Factor:**

Rugged

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

7 oclock all primaries

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Precious Material And Location:**

Terminals surface gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0