NSN 5905-01-124-9217

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-124-9217 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.187 inches **Body Width:** 0.375 inches **Body Height:** 0.375 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 262.0 **Maximum Starting Torque:** 5.00 inch-ounces **Fragility Factor:** Rugged **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 100.0 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Ambient Tempurature In Deg Celsius Per Section At Full R
70.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-01-124-9217

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0