## NSN 5905-01-125-2398

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-125-2398
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
20.000 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.145 inches and 0.215 inches
Body Length:
0.740 inches
Body Width:
0.270 inches
Body Height:
0.135 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
1.400 total network
Terminal Width:
Between 0.015 inches and 0.022 inches
Identical Value Resistor Quantity:
7 each resistor
Style Designator:
Dual inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/1 government specification

## NSN 5905-01-125-2398

Film Fixed Resistor Network - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0