Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-125-3656

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

0.938 inches

### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

## Mounting Bushing Length:

0.219 inches

## Body Length:

0.406 inches

## Shaft Style:

Round, slotted, knurled

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

100.000 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

Between 295.0 and 305.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# Power Dissipation Rating Per Section In Watts:

0.3 free air single section

# **Resistance Tolerance Per Section In Percent:**

-30.0/+30.0 single section

# NSN 5905-01-125-3656

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0