## NSN 5905-01-126-2303

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-126-2303 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.688 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.250 inches **Screw Thread Series Designator:** 

**Screw Thread Diameter:** 0.250 inches Unef Screw Thready Qty Per Inch (tpi): 32.0

## NSN 5905-01-126-2303

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Features Provided:	
Humidity proof	
Electrical Resistance Per Section:	
5.0 ohms single section	
Rotary Actuator Travel In Angular Deg:	
300.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
340.0 single section	
Power Dissipation Rating Per Section In Watts:	
12.5 heat sink single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
25.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment	ental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
2 tab, solder lug	
Specification Data:	
81349-mil-r-22/1 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	