NSN 5905-01-126-3634

Section Quantity:

First Flat Length:

Cylindrical bushing mounted

Body Style:

0.438 inches
Flat Height:
0.218 inches
Body Diameter:
1.094 inches

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-126-3634

Shaft Diameter:
0.250 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
8.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Mounting Method:
Shaft w/panel seal
Features Provided:
Switch
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 330.0 and 340.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

NSN 5905-01-126-3634

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: