NSN 5905-01-126-7772

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-126-7772

Out to Out to
Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.499 inches and 1.500 inches
Shaft Diameter:
Between 0.2494 inches and 0.2498 inches
Shaft Length:
0.650 inches
Body Length:
1.000 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:

520.0 ohms single section

NSN 5905-01-126-7772

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
360.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
105.0 single section	
Power Dissipation Rating Per Section In Watts:	
4.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A002a0	