Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-127-0006

Section	Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### Terminal Length:

0.312 inches

**Body Diameter:** 

0.250 inches

**Body Length:** 

0.180 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

215.0

### Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

**Mounting Method:** 

Terminal

Electrical Resistance Per Section:

3.0 percent, rated amperes c and better flooring

### Rotary Actuator Travel In Angular Deg:

270.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

# **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

## Standard Taper Curve Per Section:

A single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0