

View Online at <https://aerobasegroup.com/nsn/5905-01-127-1837>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

0.781 inches

Undercut Width:

Between 0.0570 inches and 0.0670 inches

Body Diameter:

Between 0.840 inches and 0.850 inches

Shaft Diameter:

Between 0.245 inches and 0.248 inches

Shaft Length:

Between 1.559 inches and 1.621 inches

Body Length:

0.625 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.8800 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Undercut Diameter:

Between 0.116 inches and 0.117 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.27 inch-ounces

Maximum Running Torque:

0.27 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Fragility Factor:

Moderately rugged

Undercut Length:

Between 0.105 inches and 0.115 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

6.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

336.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

150.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

89305-484829 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0