

View Online at <https://aerobasegroup.com/nsn/5905-01-127-1838>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Terminal Length:

0.125 inches

Undercut Diameter:

Between 0.740 inches and 0.750 inches

Undercut Width:

Between 0.0570 inches and 0.0670 inches

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

Between 1.559 inches and 1.621 inches

Body Length:

Between 0.490 inches and 0.500 inches

Mounting Lip Diameter:

Between 0.7495 inches and 0.7500 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

351.0

Maximum Starting Torque:

0.27 inch-ounces

Maximum Running Torque:

0.27 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Front end

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

0.221 cubic inches

Electrical Resistance Per Section:

6.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

336.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

89305-484830 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0