## NSN 5905-01-127-1977

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-127-1977 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.2500 inches Pilot Length: 0.0300 inches **Undercut Diameter:** 0.745 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** Between 0.344 inches and 0.406 inches **Body Length:** 0.500 inches **Mounting Lip Diameter:** Between 0.7450 inches and 0.7500 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 

0.27 inch-ounces **Maximum Running Torque:** 0.27 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches

## NSN 5905-01-127-1977

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.221 cubic inches
Electrical Resistance Per Section:
6.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
336.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 turret
Shalf Life:

N/a

## NSN 5905-01-127-1977

Precision Nonwire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0