

View Online at <https://aerobasegroup.com/nsn/5905-01-127-3726>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.516 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

295.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+5.5 -55 degrees celsius single section and +0.0/+4.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0