Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-127-7053

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

2.625 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.500 inches

#### Body Length:

3.500 inches

#### Shaft Style:

Round

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

## **Mounting Method:**

Standard bushing

# Features Provided:

Hermetically sealed

# **Electrical Resistance Per Section:**

20.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-2.0/+2.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0