## NSN 5905-01-128-8908

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-128-8908

Tompurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0 Electrical Resistance: 931.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 fice air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Electrical Resistance: 931.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 fice air Unpackaged Unit Welght: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Avial terminal each end Test Data Document:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.1000 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4.175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.001  Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end Test Data Document:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end Test Data Document:
Terminal Type: Wire lead  Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.001  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end  Test Data Document:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document:
Established  Reliability Failure Rate Level In Percent:  0.001  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end  Test Data Document:
Reliability Failure Rate Level In Percent:  0.001  Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end  Test Data Document:
Terminal Length: 1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.350 grams  Style Designator: Axial terminal each end  Test Data Document:
Terminal Length:  1.500 inches  Body Diameter:  0.109 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
1.500 inches  Body Diameter: 0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
Body Diameter:  0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
0.109 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
0.250 inches  Power Dissipation Rating In Watts: 0.100 free air  Unpackaged Unit Weight: 0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
Power Dissipation Rating In Watts:  0.100 free air  Unpackaged Unit Weight:  0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
0.100 free air  Unpackaged Unit Weight:  0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
Unpackaged Unit Weight:  0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
0.350 grams  Style Designator:  Axial terminal each end  Test Data Document:
Style Designator:  Axial terminal each end  Test Data Document:
Axial terminal each end  Test Data Document:
Test Data Document:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-55182/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-128-8908

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0