

View Online at <https://aerobasegroup.com/nsn/5905-01-129-2373>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.040 inches and 0.060 inches

Body Length:

1.125 inches

Body Width:

0.195 inches

Body Height:

0.344 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

8640.0

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Unthreaded hole

Center To Center Distance Between Terminal Rows:

Between 0.090 inches and 0.110 inches

Cubic Measure:

0.075 cubic inches

Electrical Resistance Per Section:

100.0 ohms single section

Rotary Actuator Travel In Angular Deg:

8640.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.7 free air single section

Resistance Tolerance Per Section In Percent:

-2.0/+2.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0