## NSN 5905-01-129-4937

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-129-4937 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.135 inches **Body Length:** 0.298 inches **Body Width:** 0.434 inches **Body Height:** 0.360 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 15.00 inch-ounces **Center To Center Distance Between Terminals:** 0.300 inches **Fragility Factor:** Moderately delicate **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Cubic Measure:** 

0.047 cubic inches

**Electrical Resistance Per Section:** 

20.000 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

270.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.150 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## NSN 5905-01-129-4937

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: