Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-130-5301	
Section Quantity:	
1	
Body Style:	
Rectangular	
Reliability Indicator:	
Not established	
Terminal Length:	
0.187 inches	
Shaft Diameter:	
0.062 inches	
Shaft Length:	
Between 0.040 inches and 0.060 inches	
Body Length:	
0.250 inches	
Body Width:	
0.218 inches	
Body Height:	
0.250 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
9000.0	
Maximum Starting Torque:	
5.00 inch-ounces	
Maximum Running Torque:	
5.00 inch-ounces	
Center To Center Distance Between Terminals:	
0.200 inches	
Terminal Location:	
Right adjacent side two rows	
Mounting Method:	
Terminal	
Center To Center Distance Between Terminal Rows:	
0.100 inches	
Electrical Resistance Per Section:	
1.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
9000.0	
Center To Center Distance Between Center Terminal And Outside T	erminal:
0.100 inches	



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0