

View Online at <https://aerobasegroup.com/nsn/5905-01-130-7625>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.969 inches

**Overall Height:**

1.031 inches

**Overall Width:**

0.625 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

1.000 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.969 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Maximum Starting Torque:**

3.00 inch-ounces

**Maximum Running Torque:**

3.00 inch-ounces

**Maximum Stop Torque:**

64.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.305 inches

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Double pole, double throw

**End Application:**

Oliver perry class ffg, spruance class dd (963), forrestal class cv, virginia class cgn (41), emory s. Land class as, los angeles class ssn (688), sturgeon class ssn (637), tarawa class lha, kidd class ddg

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Right-left adjacent sides

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0/+7.0 -55 degrees celsius single section and +0.0/+5.5 120 degrees celsius single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Switch Current Type And Rating In Amps:**

2.000 ac

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0