## NSN 5905-01-130-8375

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-130-8375 **Section Quantity:** 2 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.300 inches **Terminal Length:** 0.120 inches **Overall Height:** 0.300 inches **Overall Width:** 0.480 inches **Body Length:** 0.190 inches **Body Width:** 0.480 inches **Body Height:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 230.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Center To Center Distance Between Terminals:** 0.300 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 50.0 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 

230.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

## NSN 5905-01-130-8375

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -100.0/+100.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.25 free air all sections **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 all sections **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 8 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No