## NSN 5905-01-131-3865

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-131-3865

Section Quantity:
1
Body Style:
Cylindrical friction mounted
Reliability Indicator:
Not established
Terminal Length:
0.250 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.562 inches
Body Length:
1.062 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.625 inches
End Application:
Speed control unit for main propulsion motor onobard 140 ft wtgb coast guard vessels
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Friction
Electrical Resistance Per Section:
20000.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.312 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
10.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:

4 pin

## NSN 5905-01-131-3865

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0