Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-131-4349

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.175 inches

Shaft Diameter:

0.100 inches

Shaft Length:

0.060 inches

Body Length:

0.750 inches

Body Width:

0.190 inches

Body Height:

0.250 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Maximum Starting Torque:

8.00 inch-ounces

Center To Center Distance Between Terminals:

0.500 inches

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.000 ohms single section

Rotary Actuator Travel In Angular Deg:

5400.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0