## NSN 5905-01-131-8050

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-131-8050

Section Quantity
Section Quantity:
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.500 inches
Terminal Length:
0.500 inches
Overall Height:
1.125 inches
Overall Width:
0.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
265.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Screw Thread Diameter:
0.375 inches

## NSN 5905-01-131-8050

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	
Standard bushing	
Center To Center Distance Between Terminal Rows:	
0.200 inches	
Electrical Resistance Per Section:	
5.0 percent, rated amperes c and better flooring	
Rotary Actuator Travel In Angular Deg:	
300.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.200 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-150.0/+150.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 7th secondary quality	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	