## NSN 5905-01-132-4125

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-132-4125

Electrical Resistance: 162.000 ohms Resistance Tolerance In Percent: 1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 170.0 Tempurature Range Of	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 17.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.00 Itempurature Range Of Tempurature Coefficient In Deg Celsius: 15.50-4-150.0 Inclosure Method: Incapsulated Iteminal Type: If Iteminal Type: If Iteminal Type: Iteminal Iteminal Type: Iteminal Iteminal Iteminal Iteminal Iteminal Type: Iteminal Itemina	-100.0/+100.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/-150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/-150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/-150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/-150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0 Tempurature Range Of Temp	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power:  7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  7.0.0 Fempurature Range Of Tempurature Range	162.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  170.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0/+150.0  Inclosure Method:  Incapsulated  Terminal Type:  Wiffire Isad  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  30dy Diameter:  10.190 inches  30dy Length:  10.562 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Avial terminal each end  Test Data Document:  3149-milr-3901773 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via Juit Of Measure:  - Demilitarization:  No	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficie	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.001  30dy Diameter: 0.190 inches  30dy Diameter: 0.190 inches  30dy Length: 0.562 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator:  Aktal terminal each end  Test Data Document: 31349-mili-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain service mental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:  - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  nclosure Method: Encapsulated  Ferminal Type: Wire lead  Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  30dy Diameter: 0.190 inches 30dy Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mili-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Unit Of Measure: - Demilitarization: No	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4150.0  nclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  80dy Diameter:  0.190 inches  80dy Length:  0.562 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Jint Of Measure:  Demilitarization:  No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 191349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: W/a Juit of Measure: - Demilitarization: No	150.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mill-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormati; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 30dy Diameter: 0.190 inches 30dy Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Fest Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit of Measure:	-55.0/+150.0
Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  3ody Diameter:  0.190 inches  3ody Length:  0.562 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Avial terminal each end  Fest Data Document:  31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Juit Of Measure:  Demilitarization:	Inclosure Method:
Are lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: - Demilitarization: No	Encapsulated
Reliability Indicator:  Established Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.190 inches Body Length:  0.562 inches Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:	Terminal Type:
Established Reliability Failure Rate Level In Percent:	Wire lead
Reliability Failure Rate Level In Percent:  0.001  3ody Diameter:  0.190 inches  3ody Length:  0.562 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Reliability Indicator:
Body Diameter:  D.190 inches  Body Length: D.562 inches  Power Dissipation Rating In Watts:  D.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  B1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Established
Body Length: 0.190 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Juit Of Measure:	Reliability Failure Rate Level In Percent:
20.190 inches Body Length: 20.562 inches Power Dissipation Rating In Watts: 20.000 free air Bytel Designator: Axial terminal each end Fest Data Document: 20.1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.001
Body Length:  0.562 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.190 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:	Body Length:
Style Designator: Axial terminal each end  Test Data Document: B1349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	0.562 inches
Axial terminal each end  Fest Data Document:  31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Fest Data Document:  81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.000 free air
Fest Data Document:  81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  8helf Life:  N/a  Unit Of Measure:  Demilitarization:	Style Designator:
31349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	81349-mil-r-39017/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a  Jnit Of Measure:  -  Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fila:	No
·· <del>9</del> ·	Fiig:
A001a0	A001a0