## NSN 5905-01-132-4778

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-132-4778					
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:					
-300.0/+300.0					
Electrical Resistance:					
47.000 kilohms					
Resistance Tolerance In Percent:					
-5.000/+5.000					
Ambient Tempurature In Deg Celsius At Full Rated Power:					
70.0					
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:					
125.0					
Tempurature Range Of Tempurature Coefficient In Deg Celsius:					
-55.0/+125.0					
Inclosure Method:					
Encapsulated					
Terminal Quantity:					
14					
Terminal Type:					
Tab, solder lug					
Reliability Indicator:					
Not established					
Terminal Length:					
Between 0.145 inches and 0.215 inches					
Body Length:					
0.740 inches					
Body Width:					
0.270 inches					
Body Height:					
0.135 inches					
Schematic Diagram Designator:					
Ladder network					
Power Dissipation Rating In Watts:					
1.300 total network					
Terminal Width:					
Between 0.015 inches and 0.022 inches					
Identical Value Resistor Quantity:					
13 each resistor					
Style Designator:					
Dual inline					
Test Data Document:					
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification					
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain					

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/1 government specification

## NSN 5905-01-132-4778

Film Fixed Resistor Network - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0