NSN 5905-01-134-5080

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-134-5080 **Section Quantity: Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.875 inches **Body Length:** 1.122 inches **Body Width:** 0.620 inches **Body Height:** 0.620 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 305.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Right-left adjacent sides **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-01-134-5080

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resi	istance	То	lerance	Per	Sect	ion	ln	Per	cen	t:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0