NSN 5905-01-135-7031

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-135-7031

Electrical Resistance: .810 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Terminal Type: Wire lead Reflability Indicator: Established Reflability Failure Rate Level In Percent: 10.001 30dy Diameter: 10.001 inches 30dy Length: 10.250 inches Power Dissipation Rating In Watts: 10.100 free air Style Designator: 10.4149-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4.1000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/175.0 Tempurature Range Of Tempuratur	-50.0/+50.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Idermetically sealed Terminal Type: Wire lead Reliability Indicator: Istablished Reliability Failure Rate Level In Percent: 1.001 30dy Diameter: 1.010 inches 30dy Length: 1.250 inches 70ver Dissipation Rating In Watts: 1.010 free air Reliability Test Date Document: 1.4149-mill-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain inviviconmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.001 30dy Diameter: 1.109 inches 30dy Length: 1.250 inches 70der Dissipation Rating In Watts: 1.100 free air Style Designator: xxial terminal each end Test Data Document: 1xi49-milr-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain invivronmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	6.810 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4175.0 Inclosure Method: Idermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 80dy Diameter: 10.109 inches Rough Length: 10.250 inches Power Dissipation Rating In Watts: 10.100 free air Style Designator: 10.4404-milk-r55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Sody Diameter: 10.109 inches 30dy Length: 10.250 inches Power Dissipation Rating In Watts: 10.100 free air Style Designator: Axial terminal each end Test Data Document: 11349-milr-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: 1/4	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Idermetically sealed Terminal Type: Wire lead Reliability Indicator: Stablished Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Avial terminal each end Test Data Document: 11349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Full Rated Power:
Trempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 3.0dy Diameter: 0.109 inches 3.0dy Diameter: 0.109 inches 7.0ver Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain specification (includes requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Idermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.001 3.0dy Diameter: 1.0109 inches 3.0dy Length: 1.0250 inches Power Dissipation Rating In Watts: 1.010 free air Style Designator: xixial terminal each end Fest Data Document: 3.149-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: dermetically sealed ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Rody Diameter: 0.109 inches Rody Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	175.0
Inclosure Method: Idermetically sealed Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Rody Diameter: 0.109 inches Rody Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Reliability Established Reliability Failure Rate Level In Percent: 0.109 inches Rody Length: 0.109 inches Rody Length: 0.100 free air Reliability Failure Rate Level In Percent: 0.101 free air Reliability Failure Rate Level In Percent: 0.108 inches Rody Length: 0.109 inches Rody Length:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 109 inches Body Length: 250 inches Power Dissipation Rating In Watts: 100 free air Skyle Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	-55.0/+175.0
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 0.001 0.009 inches0.109 inches0.250 inches0.250 inches0.100 free air0.100 free air0.100 free air0.100 free air0.100 free air0.101 free air	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Rody Diameter: 0.109 inches Rody Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Reliability Failure Rate Level In Percent: 0.1100 free air Reliability Failure Rate Level In Percent: 0.1100 free air Reliability Failure Rate Level In Percent: 0.1100 free air Reliability Failure Rate Level In Percent: 0.1100 free air Reliability Failure Rate Level In Percent: 0.1100 free air 0	Hermetically sealed
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Rody Diameter: 0.109 inches Rody Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Reliability Failure Rate Level In Percent: 0.101 free air Reliability Failure Rate Level In Percent: 0.102 inches Power Dissipation Rating In Watts: 0.100 free air Reliability Failure Rate Level In Percent: 0.100 free air Reliability Failure Rate Level In Percent: 0.100 free air 0.1	Terminal Type:
Reliability Failure Rate Level In Percent: 0.001 3ody Diameter: 0.109 inches 3ody Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a	Wire lead
Reliability Failure Rate Level In Percent: 2.001 3.004 Diameter: 2.0109 inches 3.005 Length: 2.0250 inches 2.0260 inches 2.0260 inches 2.0270 inches	Reliability Indicator:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.1349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa	Established
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Reliability Failure Rate Level In Percent:
2.0.109 inches Body Length: 2.250 inches Power Dissipation Rating In Watts: 2.100 free air Style Designator: Axial terminal each end Fest Data Document: 2.1349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.001
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Body Diameter:
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.109 inches
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Body Length:
O.100 free air Style Designator: Axial terminal each end Fest Data Document: B1349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.250 inches
Axial terminal each end Fest Data Document: B1349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.100 free air
Test Data Document: B1349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Style Designator:
81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Axial terminal each end
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	81349-mil-r-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	Shelf Life:
Jnit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No.	No
ilig:	Fiig:
A001a0	A001a0