NSN 5905-01-136-1276

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-136-1276 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** Between 0.132 inches and 0.180 inches **Body Diameter:** 0.410 inches **Body Length:** 0.166 inches **Shaft Bearing Type:** Bearing **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 225.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Cubic Measure:** 0.009 cubic inches **Electrical Resistance Per Section:** 1.0 megohms single section **Rotary Actuator Travel In Angular Deg:** 225.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

90.0 single section

NSN 5905-01-136-1276

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.15 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No