NSN 5905-01-136-2587

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-136-2587 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 0.844 inches and 0.906 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.497 inches **Mounting Bushing Length:** Between 0.305 inches and 0.325 inches **Body Length:** Between 1.105 inches and 1.145 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a
Unit Of Measure:

NSN 5905-01-136-2587

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A002a0