Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-136-2587

| View Online at https://aerobasegroup.com/nsn/5905-01-136-2587 |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| Between 0.844 inches and 0.906 inches |
| Shaft Diameter: |
| Between 0.248 inches and 0.250 inches |
| Shaft Length: |
| 0.497 inches |
| Mounting Bushing Length: |
| Between 0.305 inches and 0.325 inches |
| Body Length: |
| Between 1.105 inches and 1.145 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0