Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-136-6473

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0 first temp coefficient

Electrical Resistance:

1.000 megohms

Resistance Tolerance In Percent:

-5.000/+5.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient

Inclosure Method:

Encapsulated

Terminal Quantity:

16

Terminal Type:

Tab, solder lug

Reliability Indicator:

Not established

Terminal Length:

Between 0.190 inches and 0.215 inches

Body Length:

0.830 inches

Body Width:

0.270 inches

Body Height:

0.135 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

1.500 total network

Terminal Width:

Between 0.015 inches and 0.022 inches

Identical Value Resistor Quantity:

15 each resistor

Style Designator:

Dual inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/2 government specification

NSN 5905-01-136-6473

Film Fixed Resistor Network - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0