Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-136-7432

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### **Body Length:**

1.125 inches

#### Shaft Style:

Round, slotted

#### Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

#### **Terminal Location:**

Longitudinally positioned on the circumference

#### **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

5.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

3600.0

## Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

#### **Function Conformity Per Section:**

Single section independent linearity

#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

#### **Function Characteristic Per Section:**

Single section linear

## **Terminal Type And Quantity:**

3 tab, solder lug

## Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5905-01-136-7432

Precision Wire Wound Variable Resistor - Page 2 of 2

AeroBase Group

**Fiig:** A002a0