Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-137-0858

| Section | Quantity: |
|---------|-----------|

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.180 inches

Body Diameter:

0.250 inches

**Body Length:** 

0.250 inches

Actuator Type:

Flush drive with slot-hole

#### **Maximum Starting Torque:**

3.00 inch-ounces

### Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

#### Mounting Method:

Terminal

#### **Electrical Resistance Per Section:**

100.000 kilohms single section

## Rotary Actuator Travel In Angular Deg:

270.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

### Standard Taper Curve Per Section:

A single section

AeroBase Group

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0