NSN 5905-01-138-3274

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-138-3274 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.766 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.734 inches **Overall Diameter:** 1.312 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 348.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.00700 inches **Shaft Runout:**

0.0025 inches **Lateral Runout:** 0.003 inches

NSN 5905-01-138-3274

Precision Nonwire Wound Variable Resistor - Page 2 of 3



| Pilot Diameter Runout: |
|---|
| 0.00250 inches |
| Shaft Radial Play: |
| 0.004 inches |
| Fragility Factor: |
| Moderately rugged |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Humidity proof |
| Electrical Resistance Per Section: |
| 10.000 percent, rated amperes c and better flooring |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.50/+0.50 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -4000.0/+4000.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 7th secondary quality |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| 7 oclock all primaries |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 65.0 single section |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| |

NSN 5905-01-138-3274

Precision Nonwire Wound Variable Resistor - Page 3 of 3



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0