Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-139-5072

# Section Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

0.187 inches

**Body Diameter:** 

0.250 inches

**Body Length:** 

0.250 inches

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Maximum Starting Torque:

5.00 inch-ounces

### Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.141 inches

### **Terminal Location:**

Rear end

#### Mounting Method:

Terminal

#### Center To Center Distance Between Terminal Rows:

0.071 inches

#### Features Provided:

Hermetically sealed

#### **Electrical Resistance Per Section:**

50.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.071 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0