NSN 5905-01-139-5077

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-139-5077

Section Quantity:
1 Parks Outes
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.625 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.796 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
325.0
Maximum Starting Torque:
21.00 inch-ounces
Maximum Running Torque:
21.00 inch-ounces
Maximum Stop Torque:
96.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.312 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained

NSN 5905-01-139-5077

No Fiig:

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
325.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+4.0 -40 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section
and -2.5/+2.5 85 degrees celsius single section and -3.0/+3.0 105 degrees celsius single section and -4.0/+4.0 120 degrees celsius single
section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
1.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization: