NSN 5905-01-140-0571

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-140-0571

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.219 inches
Terminal Length:
0.500 inches
Overall Height:
1.125 inches
Overall Width:
0.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.594 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
2.50 inch-ounces
Maximum Running Torque:
2.50 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces

Nonturn Device Location: At 3 oclock and at 9 oclock

NSN 5905-01-140-0571

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



lonturn Device Radius:	
.375 inches	
enter To Center Distance Between Terminals:	
.200 inches	
ragility Factor:	
loderately rugged	
crew Thread Diameter:	
.375 inches	
crew Thread Series Designator:	
Inef	
crew Thready Qty Per Inch (tpi):	
2.0	
erminal Location:	
ower adjacent side two rows	
lounting Method:	
ocking bushing	
enter To Center Distance Between Terminal Rows:	
.200 inches	
eatures Provided:	
lumidity proof	
lectrical Resistance Per Section:	
00.000 percent, rated amperes c and better flooring	
otary Actuator Travel In Angular Deg:	
00.0	
enter To Center Distance Between Center Terminal And Outside Terminal:	
.100 inches	
mbient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power	:
50.0 single section	
empurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
100.0/+100.0 single section	
ower Dissipation Rating Per Section In Watts:	
.0 7th secondary quality	
esistance Tolerance Per Section In Percent:	
10.0/+10.0 single section	
ctuator Travel Control Feature:	
tops	
Imbient Tempurature In Deg Celsius Per Section At Full Rated Power:	
0.0 single section	
tandard Taper Curve Per Section:	
single section	
erminal Type And Quantity:	
pin	
helf Life:	

N/a

NSN 5905-01-140-0571

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0