

View Online at https://aerobasegroup.com/nsn/5905-01-140-0571

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

1.219 inches

#### Terminal Length:

0.500 inches

**Overall Height:** 

1.125 inches

Overall Width:

#### 0.625 inches

Shaft Diameter:

# 0.250 inches

Shaft Length:

0.625 inches

#### Mounting Bushing Length:

0.500 inches

#### Body Length:

0.594 inches

## Body Width:

0.625 inches

#### **Body Height:**

0.625 inches

#### Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

260.0

#### Maximum Starting Torque:

2.50 inch-ounces

#### Maximum Running Torque:

2.50 inch-ounces

#### Maximum Stop Torque:

64.00 inch-ounces

## Nonturn Device Location:

At 3 oclock and at 9 oclock

# NSN 5905-01-140-0571

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.375 inches
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Locking bushing
Center To Center Distance Between Terminal Rows:
0.200 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
100.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0