

NSN 5905-01-140-1366 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-140-1366 **Section Quantity:**

Section Quantity.
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.202 inches
Shaft Diameter:
Between 0.050 inches and 0.065 inches
Shaft Length:
Between 0.050 inches and 0.055 inches
Body Length:
Between 0.410 inches and 0.420 inches
Body Width:
Between 0.185 inches and 0.200 inches
Body Height:
Between 0.370 inches and 0.380 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section

0.25 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-140-1366

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: