NSN 5905-01-141-9391

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-141-9391

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.625 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.625 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
325.0
Maximum Starting Torque:
20.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
96.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.313 inches
Switch Operating Position:
Start of rotation

0.250 inches

Switch Contact Arrangement:

Screw Thread Diameter:

Single pole, single throw, normally closed

NSN 5905-01-141-9391

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Cubic Measure:
0.244 cubic inches
Electrical Resistance Per Section:
20.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
325.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+4.0 -40 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section
and -2.5/+2.5 85 degrees celsius single section and -3.0/+3.0 105 degrees celsius single section and -4.0/+4.0 120 degrees celsius single
section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
1.000 ac/dc
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No