NSN 5905-01-142-4933

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-142-4933

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -300.0/+300.0 |
| Electrical Resistance: |
| 3.770 kilohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 40.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 250.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+250.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reactance Characteristic: |
| Inductive |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| |
| Between 0.225 inches and 0.265 inches |
| Between 0.225 inches and 0.265 inches Body Length: |
| |
| Body Length: |
| Body Length: Between 1.500 inches and 1.850 inches |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): 0.475 cubic inches |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): 0.475 cubic inches Unpackaged Unit Weight: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): 0.475 cubic inches Unpackaged Unit Weight: 15.000 grams |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): 0.475 cubic inches Unpackaged Unit Weight: 15.000 grams Style Designator: |
| Body Length: Between 1.500 inches and 1.850 inches Body Width: Between 0.350 inches and 0.410 inches Body Height: Between 0.440 inches and 0.500 inches Power Dissipation Rating In Watts: 10.000 free air Features Provided: Mounting hardware Cubic Measure (non-core): 0.475 cubic inches Unpackaged Unit Weight: 15.000 grams Style Designator: Terminals each end |

--

NSN 5905-01-142-4933

Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0