Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-142-4984

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0

### **Electrical Resistance:**

226.000 ohms

### **Resistance Tolerance In Percent:**

-1.000/+1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

### Inclosure Method:

Encapsulated

### Terminal Type:

Wire lead

# Reliability Indicator:

Established

### Reliability Failure Rate Level In Percent:

0.001

#### **Terminal Length:**

1.500 inches

#### Body Diameter:

Between 0.281 inches and 0.343 inches

#### **Body Length:**

Between 0.813 inches and 0.937 inches

#### **Power Dissipation Rating In Watts:**

5.000 free air

#### Cubic Measure (non-core):

0.067 cubic inches

#### Unpackaged Unit Weight:

5.0 grams

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-39007/6 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0