## NSN 5905-01-143-3985

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-143-3985 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Maximum Stop Torque:** 192.00 inch-ounces **Mechanical Backlash In Deg Angular Rotation:** 3.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 250.000 percent, rated amperes c and better industrial clears **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 

6 tab, solder lug Shelf Life:

N/a

## NSN 5905-01-143-3985

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0