NSN 5905-01-144-1138

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-144-1138 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 2.031 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.313 inches **Body Length:** 2.031 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.750 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:**

0.002 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.002 inches **Screw Thread Diameter:** 0.375 inches

NSN 5905-01-144-1138

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: 2zzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: 2zzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Mounting Method: Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: 2zzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Standard bushing Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Electrical Resistance Per Section: 5.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
8.0 kilohms all sections Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: 2zzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Rotary Actuator Travel In Angular Deg: 360.0 Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Conformity Tolerance Per Section: -0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-0.10/+0.10 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 all sections Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Power Dissipation Rating Per Section In Watts: 4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
4.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
All sections independent linearity Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Resistance Tolerance Per Section In Percent: -1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-1.0/+1.0 all sections Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Actuator Travel Control Feature: Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Continuous motion Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Criticality Code Justification: Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Zzzy Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3215
Terminal Type And Quantity:
6 turret
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No .
Fiig: