## NSN 5905-01-144-3838

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-144-3838

Tempurature	Coefficient	Of Resistance	In Ppm	Per Deg	g Celsius:
-------------	-------------	---------------	--------	---------	------------

-100.0/+100.0 first temp coefficient

**Electrical Resistance:** 

10.000 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0/+150.0 temp range of first temp coefficient

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.001

**Terminal Length:** 

Between 1.000 inches and 1.625 inches

**Body Diameter:** 

Between 0.082 inches and 0.098 inches

**Body Length:** 

Between 0.204 inches and 0.300 inches

**Power Dissipation Rating In Watts:** 

0.250 free air

**Special Features:** 

Cubic measure is 0.002 cubic inches

Style Designator:

Axial terminal each end

**Test Data Document:** 

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-r-39017/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5905-01-144-3838

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0