NSN 5905-01-145-4143

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-145-4143

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.500 inches
Terminal Length:
0.250 inches
Overall Height:
0.766 inches
Overall Width:
0.516 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.500 inches
Body Width:
0.516 inches
Body Height:
0.516 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
265.0
Maximum Starting Torque:
4.50 inch-ounces
Maximum Running Torque:
4.50 inch-ounces
Maximum Stop Torque:
16.00 inch-ounces
Nonturn Device Location:

At 9 oclock

NSN 5905-01-145-4143

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.245 inches
Center To Center Distance Between Terminals:
0.200 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single
section and +0.0/+3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5905-01-145-4143

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0