## NSN 5905-01-145-9828

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-145-9828

view Online at https://derobasegroup.com/nsi//3303-01-143-3020
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0
Electrical Resistance:
24.900 ohms
Resistance Tolerance In Percent:
-3.000/+3.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.313 inches and 0.437 inches
Body Diameter:
Between 0.844 inches and 0.906 inches
Between 0.844 inches and 0.906 inches  Mounting Bushing Length:
Mounting Bushing Length:
Mounting Bushing Length: 0.783 inches
Mounting Bushing Length: 0.783 inches Body Length:
Mounting Bushing Length: 0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches
Mounting Bushing Length: 0.783 inches  Body Length: Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):  0.488 cubic inches
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):  0.488 cubic inches  Unpackaged Unit Weight:
Mounting Bushing Length:  0.783 inches  Body Length: Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):  0.488 cubic inches  Unpackaged Unit Weight:  22.0 grams
Mounting Bushing Length:  0.783 inches  Body Length: Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):  0.488 cubic inches  Unpackaged Unit Weight:  22.0 grams  Style Designator:
Mounting Bushing Length:  0.783 inches  Body Length:  Between 0.781 inches and 0.843 inches  Power Dissipation Rating In Watts:  25.000 free air  Terminal Width:  0.140 inches  Mounting Bushing Diameter:  0.625 inches  Cubic Measure (non-core):  0.488 cubic inches  Unpackaged Unit Weight:  22.0 grams  Style Designator:  Axial terminals one end

--

## NSN 5905-01-145-9828

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0