Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-145-9850

## Section Quantity:

1

Body Style:

Rectangular

### **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.188 inches

#### Shaft Diameter:

0.080 inches

#### Shaft Length:

0.060 inches

#### **Body Length:**

0.375 inches

#### Body Width:

0.190 inches

## Body Height:

0.375 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

10.000 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

9000.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### Standard Taper Curve Per Section:

A single section

#### **Terminal Type And Quantity:**

3 pin

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

## Fiig:

A002a0